

NEW OPENING CHECKLIST

CONTRACTOR: _____

PROJECT: _____

CONTACT: _____ **PHONE:** _____ **EMAIL:** _____

FRAMES

	ALUMINUM		HOLLOW METAL			
Opening Size:	3/0 x 6/8	3/0 x 7/0	3/0 x 8/0	6/0 x 6/8	6/0 x 7/0	Other
(Finished Opening = inside frame dimension after install)						
Throat Size:	3 1/2	3 3/4	4 5/8	4 7/8	Other	
(Throat Size = wall thickness) (Width of stud + total drywall thickness)						
Face:	2"	1 1/2"				
Handing:	LH	RH	LHR	RHR		
Rating:	Fire: N/R	20	45	60	90	
STC:						

*TO HAND A DOOR
FACE THE DOOR FROM THE OUTSIDE OR KEY SIDE*



DOORS







	Wood		Hollow Metal			
Veneer:	Paint Grade	Birch	Cherry	Mahogany	Maple	Oak
	Other - Specify: _____					
Cut:	Rotary	Plain Sliced	Quarter	Rift		
(Often, a label may be found on top of an existing door with useful information)						
Opening Size:	To match frame opening size listed above. We will prefit and undercut doors according to the frame opening size.					
Handing:	LH	RH	LHR	RHR		
Rating:	Fire: N/R	20	45	60	90	
STC:						
Features: Lite:	Width	Height	Lockstile	Top Rail		
Louver:	Width	Height	Lockstile	Btm Rail		

COMMON DOOR VENEERS










NEW OPENING CHECKLIST

HARDWARE

Finish:	US26D	US26	US3	US4	US10	US10B
	 <small>626 Satin Chrome</small>	 <small>625 Polished Chrome</small>	 <small>605 Polished Brass</small>	 <small>606 Satin Brass</small>	 <small>612 Satin Bronze</small>	 <small>613 Oil Rubbed Bronze</small>
	OTHER - SPECIFY					

Hinges:	Size:	Std:	Hvy:	Pivots:	Other:
---------	-------	------	------	---------	--------

	Locks:	Cylindrical	Mortise	Exit Device		
Lock Function:		10 - Passage	40 - Privacy	53 - Office	80 - Storeroom	
		 <small>Both levers always unlocked</small>	 <small>- Latch by either lever unless outside lever is locked by push button in inside lever - Turning inside lever or closing door releases button - Emergency button in outside lever unlocks with use of a blade screwdriver in outside lever and releases inside button</small>	 <small>- Deadlocking latch - Latch by either lever unless outside lever is locked by push/turn button in inside lever - Push button released by key outside or lever inside</small>	 <small>- Deadlocking latch - Latch by lever inside or key outside - Outside lever rigid at all times</small>	
Lever Design:		Saturn	Neptune	Jupiter	Other	
						

Aux HARDWARE

Door Closers:	Surface	Concealed	Wall Stop	Floor Stop	
Protection Plates:	Push/Pull	Size x	Kick Plate	Size x	
Gasketing:	Seals	Threshold	Door Bottom	Edge Guard	

NOTES:
